



WDS COMPONENTS
THE HOME OF STANDARD PARTS & MACHINE ACCESSORIES

WDS 954



Description

Material:

316 Stainless Steel

Version:

Stainless Steel Detent Pin

Quick Release Pin - Inch Specifications

Pin Diameter (inches)	Double Shear Min. Steel	Double Shear Min. Stainless	Recommended Hole Diameter (Max)	Recommended Hole Diameter (Min)
3/16	4,600	5,150	0.1940	0.1900
1/4	8,200	9,200	0.2540	0.2500
5/16	12,800	14,400	0.3165	0.3125
3/8	18,400	20,600	0.3790	0.3750
7/16	25,000	28,000	0.4425	0.4375
1/2	32,800	36,800	0.5050	0.5000
9/16	41,200	46,000	0.5675	0.5625
5/8	51,200	57,500	0.6300	0.6250
3/4	73,600	82,500	0.7570	0.7500
7/8	100,000	112,500	0.8820	0.8750
1	131,000	147,000	1.0100	1.000

Quick Release Pin - Metric Specifications

Pin Diameter (mm)	Double Shear Min (N) Steel	Double Shear (N) Stainless	Recommended Hole Diameter (Max)	Recommended Hole Diameter (Min)
5	21,720	24,440	5.1	5
6	31,690	35,650	6.1	6
8	56,700	63,790	8.1	8
10	88,940	100,060	10.1	10
12	128,460	144,520	12.1	12
16	229,150	257,800	16.1	16
20	358,790	403,640	20.15	20
25	561,440	631,620	25.15	25

Contact Us:

wdscomponents.com

Sales Team: 0333 043 5443

sales@wdscomponents.com